Consumer and Corporate Affairs Canada

Bureau des brevets

Ottawa, Canada K1A 0C9 Patent Office

(21)	(A1)	2,099,389
(22)		1993/06/20

(43) 1994/12/31

5,085,4/85

- (51) INTL.CL. 5 A01M-001/08
- (19) (CA) APPLICATION FOR CANADIAN PATENT (12)
- (54) Flying Insect Exterminator
- (72) Biela, Paul Canada ;
- (71) Same as inventor
- (57) 12 Claims

BEST AVAILABLE COPY

Notice:

This application is as filed and may therefore contain an incomplete specification.



CCA 3254 (10-92) 41 7530-21-936-325

2099389

ABSTRACT

The invention is a device, to catch and exterminate flying insects, that is comprised of: a hollow housing that is open at its top end. A fan is secured within the housing, so that its intake end faces the top of the housing. A light source is located above and proximate the intake end of the fan. An airpermeable enclosure, the 'catcher', the inside of which may be accessed by a person who is operating the device, forms the end portion of the housing. The catcher may either be a separate air-permeable element, that is removably sealingly attached to the housing's bottom end, or it may be the bottom portion of the housing itself, which is air-permeable, and which has a closeable access port.

1

10

15

20

25

FLYING INSECT EXTERMINATOR

Background of the Invention

Field of the Invention

The present invention relates to flying insect capturing and killing devices. In particular the present invention relates to devices that capture the insect by means of suction.

Description of Related Art

Flying insects, such as mosquitoes, flies, moths, and the like, have always posed a nuisance problem to people who live in areas where those insects are found. In the last half of this twentieth century, people have increasingly turned their attention to ridding themselves of nulsance insects. In some locations, such as Winnipeg, Manitoba, Canada, hundreds of thousands of dollars are spent, annually, to spray the entire city with mosquito killing poison. Mosquitoes and other insects have been similarly attacked in other areas, at great expense to the municipality. Personal use insect killing devices have also been known for many years. Some examples include, fly paper, the fly swatter, aerosol can poison sprays. Other, more mechanized examples, include devices having a suction collection area, which draws in the insect. Many suction collection devices rely on one-way opening flaps, or connecting passages, and multiple stages, through which the captured insect must flow, before it reaches the secure holding area. Many insect trapping devices, including suction devices, also rely on a poison inside the device, to kill the insect, or on a disposable container, into

- 1 -

which the insects are drawn.

5

10

15

20

25

Summary of the Invention

A first object of the present invention, is to provide a relatively easy to construct, and inexpensive, flying insect catching and exterminating device. A second object of the invention, is to provide an environmentally friendly device, that is also effective in catching and exterminating flying insects. A third object of the invention is to construct the device so that it is relatively inexpensive to operate. A fourth object of the invention is to provide a device that requires as little maintenance as possible, with the exception of discarding the killed insects. A fifth object of the invention is to provide a device that is quiet and inoffensive in operation. A sixth object of the invention, is to provide a device that is effective against a large variety of flying insects, without the need to modify it for any of the variety of insects.

The objects of the invention are accomplished by constructing a device comprised of: a hollow housing, having an opening at its top end; a fan secured within the housing, such that the intake end of the fan faces the top of the housing; a light source above and proximate the intake end of the fan; an air-permeable, non-insect permeable, enclosure, the 'catcher', the inside of which may be accessed by a person who is operating the device, that is the terminus of the bottom portion of the housing. The catcher may either be a separate air-permeable, non-insect permeable element, that is removably sealingly attached to the housing's bottom end, or it may be the bottom

- 2 -

portion of the housing itself, which is air-permeable, and which has a closeable access port.

5

10

15

25

The insect is attracted to the light source. The fan, which is in continuous operation, creates a flow of air from its intake end, to and past its exhaust end. An insect that has been attracted to the light source, in its flight around and near the light source, will, in all but negligible instances, fly into the air stream created by the fan. The air stream then sucks the insect through the spinning fan blades and into the catcher. The insect cannot fly back up through the fan blades and out of the housing, because the spinning fan blades make such a flight impossible in all but the most anomalous of situations, and the air stream that was strong enough to suck the insect down, is in continuous existence, and therefore should be strong enough to keep the insect from flying against it, out of the housing. The air stream also continuously passes over the insect and though the air-permeable portion of the catcher, continuously dehydrating the insect, until after a sufficient time, the insect is killed from dehydration.

Periodically, as necessary, the catcher is emptied.

The only consumption of the device is the electricity required to power the light source, and to run the fan. The only anticipated maintenance, other than emptying the insects, is replacement of the light source, when it ceases to function.

Brief Description of the Drawings

Figure 1 is a perspective view of a device according to the invention, employing a mesh catcher, and a cover above

the light source.

5

10

15

20

25

Figure 2 is a perspective view of a device according to the invention, employing a sack type catcher, and a cover above the light source.

Figure 3 is a perspective view of a device according to the invention, employing a sack type catcher, a cover above the light source, and a holding means for an insect attractive substance.

Figure 4 is a perspective view of a device according to the invention, wherein the bottom portion of the housing is air-permeable.

Description of the Preferred Embodiment

Figure 1 illustrates a preferred embodiment of a device according to the invention. It is comprised of a housing 9, a light source 19, which in the preferred embodiment is a light bulb, a fan 10, fan body supports 12, which securely hold the fan approximately centrally within the housing, a cover 21, that is securely attached to the housing, a hanging means 20a, securely attached to the cover, a power cord 13, for providing electricity to run the fan and the light bulb, a mesh catcher 15b, that is sealingly attached to the housing by means of screws 30, and which has a hinged bottom opening door 22. The cover 21 is non-transparent. The insects can approach the light source through spaces 23.

The distance between the light source 23, and the tops of

the fan blades 11, is chosen such that the air stream created by the fan, is strong enough, within a distance from the light source, that the insects of interest are likely to fly, to draw in the insects, and suck them through the fan blades and into the catcher 15b. The distance between the light source and the air stream will vary depending on the insects of interest, however, the choice of said distance will be known to those familiar with the art.

1

5

10

15

25

The housing 9, and the cover 21, may each be made out of any suitable metal or other material, such as plastic. They may both be made out of the same suitable material, or they may each be made out of different ones of the suitable materials. Any commercially available fan may be used, provided it creates a sufficient air stream. The hanging means 20a, may also be made out of any suitable metal or plastic, or other material, and its means of attachment to the cover 21, will be clear to those in the art, and will vary depending on the material out of which the hanging means is made, and out of which the cover is made.

The cover 21 acts to protect the light bulb and the fan and motor from rain and other air born elements. The cord 13, supplies power to both the fan and the light bulb, its connection to the light bulb is not shown.

It can be seen that the smaller that the openings 23 are made, the greater suction will be created at them. On the other hand, they must be large enough to allow a sufficient volume of insects to fly through them, for the device to be optimally effective.

Figure 2 also illustrates a preferred embodiment of the device. In figure 2 the hanging means 20b, is attached to the

housing. Another variation in figure 2, is the location of the light bulb 19; in this embodiment it is mounted in a socket that sits at the top of the fan. The catcher 15a, of figure 2, is an air-permeable cloth sack that has an elastic edge, by which it sealingly attaches to the bottom of the housing. The catcher 15a is simply pulled down and off the housing, to be emptied, it is then slipped back onto the bottom of the housing.

Figure 3 illustrates another type of cover 17, to protect the light bulb and fan from rain and other air born elements. A further enhancement to the preferred embodiment illustrated in figure 3, is the holder 34. Holder 34 is for retaining, and exposing to the air, an attractive element, that will give off particles, or molecules, that may become air born, and which are attractive to the flying insects that the device is being used to catch and kill. It will be readily known to those in the art, what elements to place in holder 34, to further attract the insects they are building the device to catch and exterminate. The hanging means, in figure 3, is an eye bolt 20c, secured to the top of cover 17.

10

15

20

25

Figure 4 illustrates another embodiment of the device. It does not have a cover, or a hanging means. It rests on legs 31. In figure 4, there is not a separate catching element. A portion of the bottom of the housing 9, which porition is generally indicated by number 40, has located in it, air-permeable vents 33, and door 32.

In all of the embodiments, the principal of operation is the same. The light source attracts flying insects. The flying insects that have come to the light source, and have entered the air stream created by the fan, are sucked through the fan blades

and into the catcher. They cannot fly back out of the catcher due to the constant opposed air current, and due to the spinning of the fan blades. While they are in the catcher they are constantly exposed to a strong current of air passing over them and out of the catcher via its air-permeable element. The constant flow of air over the insects dehydrates and thereby kills them. The catcher is emptied as desired.

Poisons are not required to kill the insects. Electic shock, and its accompanying noise are not required to kill the insects. The device is therefore not polluting with poisons, or distracting with noise. It consumes no resources, except the electricity to run it.

10

15

20

It will readily be seen by those skilled in the art, that many different materials could be used for the catcher, depending on its construction. Such materials include, but are not limited to, plastic, cloth, and screen and wire mesh. It can also be seen that the shape of the housing may be varied, and that the shape of the catcher may be varied, and that the shape of the fan may be varied, and that the shape of the cover, if one is used, may be varied, as may the hanging means, if one is used. Many variations will be obvious, and they are included in the invention, by its claims.

CLAIMS

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

- 1. A flying insect catching and exterminating device, comprised of: a hollow housing, having an opening at its top end, and an opening at its bottom end; a fan secured within the housing, such that the intake end of the fan faces the top of the housing; a light source, above and proximate the intake end of the fan; an air-permeable open ended enclosing means; wherein the open end portion of the enclosing means is removably sealingly attachable to the housing's bottom end, and wherein the flying insects which the device was designed to catch and exterminate, cannot pass through the air-permeable portion of the enclosing means.
- 2. A flying insect catching and exterminating device, comprised of: a hollow housing, having an opening at its top end, a closed bottom end, and an openable portion near its bottom end; a fan secured within the housing, such that the intake end of the fan faces the top of the housing; a light source, above and proximate the intake end of the fan; and wherein part of the housing below the fan is air-permeable, but is not permeable to the flying insects which the device was designed to catch and exterminate.
- 3. A flying insect catching and exterminating device, comprised of: a hollow housing, having an opening at its top end, a closed bottom end with an openable portion in it; a fan secured within the housing, such that the intake end of the fan faces the top of

the housing; a light source, above and proximate the intake end of the fan; and wherein part of the housing below the fan is airpermeable, but is not permeable to the flying insects which the device was designed to catch and exterminate.

- 4. A flying insect catching and exterminating device, as described in claim 1, wherein the enclosing means is a sack made out of an air-permeable cloth.
- 5. A flying insect catching and exterminating device, as described in claim 1, wherein the enclosing means is a sack made out of an air-permeable non-cloth substance.
- 6. A flying insect catching and exterminating device, as described in claim 1, wherein the catcher is a cage, made out of a mesh material, the holes of which are too small to allow any of the insects the device was designed to catch and exterminate, to pass though them.
- 7. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised of a cover secured above the light source, such that any of the flying insects the device was designed to catch and exterminate, may enter between the cover and the intake end of the fan.
- 8. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised of a holding means suitable for holding an insect attractive substance.

- 9. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised of a cover secured above the light source, such that any of the flying insects the device was designed to catch and exterminate, may enter between the cover and the intake end of the fan, and that is also comprised of a holding means suitable for holding an insect attractive substance.
- 10. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised a hanging means, secured to the housing, by which the device may be hung from a hook.
- 11. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised of a cover secured to the housing, above the light source, such that any of the flying insects the device was designed to catch and exterminate, may enter between the cover and the intake end of the fan, and which is also comprised of a hanging means, by which the device may be hung from a hook.
- 12. A flying insect catching and exterminating device, as described in claims 1, 2, 3, 4, 5, or 6, that is also comprised of a cover secured above the light source, such that any of the flying insects the device was designed to catch and exterminate, may enter between the cover and the intake end of the fan, and that is also comprised of a holding means suitable for holding an insect attractive substance, and which is also comprised of a hanging means, by which the device may be hung from a hook.






FIG. 1








FIG. 4

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

IJ	effects in the images include but are not limited to the items checked.
	BLACK BORDERS
	IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
	FADED TEXT OR DRAWING
	BLURRED OR ILLEGIBLE TEXT OR DRAWING
	SKEWED/SLANTED IMAGES
	COLOR OR BLACK AND WHITE PHOTOGRAPHS
	GRAY SCALE DOCUMENTS
	☐ LINES OR MARKS ON ORIGINAL DOCUMENT
	☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
	□ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.